



AUTOMATIC TRANSMISSION FLUID

Energeo ATF Dex III is a new generation petroleum based product for automatic and powershift transmissions. The highest level of ATF meets both GM Dexron III with 6297-M and Ford Mercon specification M2C185A. In addition, ATF 3G/H also meet Allison C-4 fluid and is qualified as PSF specification.

Energeo ATF Dex III is recommended for mobile equipment used by utility companies, which require electrical insulating properties for hydraulic oils. ATF 3G/H provide superior wear protection for all passenger cars and light trucks requiring the use of TASA, Dexron IID, Dexron III G/H ATFs. As well as the product is recommended for use by Volkswagen, Subaru, Isuzu, Fiat, Audi, Renault, Porsche and Mercedes Benz.

APPLICATIONS/ BENEFITS

- Improves hydrolytic stability
- Outstanding anti-wear properties
- Provides excellent friction, oxidation and thermal stability
- Better cold temperature flow properties than SAE 10W motor oil

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
Specific Gravity @ 15 °C	ASTM D-4052	0.8524
Flash Point, °C	ASTM D-92	190
Pour Point, °C	ASTM D-97	-48
Kinematics Viscosity @ 40 °C (cSt)	ASTM D-445	35.22
@ 100 °C (cSt)	ASTM D-445	7.25
Viscosity Index	ASTM D-2270	172
Colour	ASTM D-1500	Red
Brookefield Viscosity @ -40 °C (cP)	ASTMD 2983	12,407

PERFORMANCE STANDARDS

• Dexron IIIM, Dexron IIIH, Dexron IIIG, Dexron IIE, Dexron IID

Available Packed Size: 18L and 200L