

DIESEL ENGINE OIL ACRO 145

Energeo Diesel Acro 145 series diesel engine oils, available in SAE 30, SAE 40 and SAE 50, provides premium quality service in both diesel and gasoline engines. It is formulated from highly refined lube base stocks and carefully selected additive package comprising antioxidant, dispersant, detergent, anti-wear and oil soot thickening control agent suitable for heavy-duty service in diesel engines found in both on-highway and off-highway vehicles and equipment.

Energeo Diesel Acro 145 series are recommended for use in over the road diesel trucks, heavy-duty construction equipment, oil field engines, farm vehicles and passenger diesel cars, as well as for mixed fleet operators to use a single line of motor oils for all vehicles.

APPLICATIONS/ BENEFITS

- Minimizes oil consumption
- Neutralizes acids from high sulfur fuel
- Promotes soot control and engine cleanliness
- Reduces maintenance by increasing drain intervals

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	TYPICAL RESULTS	
SAE Viscosity Grade	30	40
Flash Point, °C	210	210
Pour Point, °C	-24	-24
Kinematics Viscosity @ 40 °C (cSt)	103.6	143.6
Kinematics Viscosity @ 100 °C (cSt)	11.14	14.5
Viscosity Index	97	97
TBN, (mgKOH/g)	8.5	8.5

PERFORMANCE STANDARDS

- API CF