

DIESEL ENGINE OIL ACRO 155

Diesel Engine Oil Acro 155 is available in SAE 50, provides premium quality service in both diesel and gasoline engines. It is specially formulated for heavy-duty service in diesel engines found in both on-highway and off-highway vehicles and equipment. Diesel Engine Oil Acro 155 is specially blended with advanced dispersant technology to resist oil thickening caused by incomplete engine combustion, which generates soot. The dispersant minimizes sludge formation and effectively keeps particles in suspension to extend filter life.

Diesel Engine Oil Acro 155 is recommended for use in over the road diesel trucks, heavy-duty construction equipment, oil field engines, farm vehicles and passenger diesel cars, as well as for mixed fleet operators to use a single line of motor oils for all vehicles.

APPLICATIONS/ BENEFITS

- Helps extend engine life
- Flight sludge and varnish
- Contains anti-corrosion agents
- Recommended for both gasoline and diesel engines
- Minimizes piston and combustion chamber deposits.

TYPICAL CHARACTERISTICS	
TEST DESCRIPTION	TYPICAL RESULTS
SAE Viscosity Grade	50
Specific Gravity @ 15 °C	0.9
Flash Point, °C	>200
Pour Point, °C	-18
Kinematics Viscosity @ 40 °C (cSt)	210
Kinematics Viscosity @ 100 °C (cSt)	19
Viscosity Index	100
TBN(mgKOH/g)	11

PERFORMANCE STANDARDS

- API CF/SF

Available Packed Size: 18L and 200L