Product Information



A PRODUCT OF VALVOLINE INC. USA

VALVOLINE DURABLEND SAE 15W50 MOTOR OIL

Valvoline Durablend SAE 15W50 Motor Oil is formulated with a combination of high-tech synthetic and premium quality conventional basestocks combined with advanced additive technology. It helps engines maintain peak performance longer by providing improved wear control, deposit protection, volatility and low temperature flow characteristics versus conventional motor oils.

Valvoline Durablend SAE 15W50 Motor Oil provides protection under severe service conditions and meet the performance requirements of virtually all naturally aspirated, turbo charged and super charged gasoline passenger cars.

The Valvoline Durablend SAE 15W50 Motor Oil advantages

• Breakdown Resistance: Increases thermal and oxidation stability

Deposit Control: Reduces formation of sludge and varnish deposits
Wear Protection: Improves oil film strength and breakdown resistance

• Cold start Properties: Oil flows easily at low temperatures

Volatility: Lowers oil vaporization and consumption at extreme

conditions

Performance levels / Approvals	Typical Characteristics	
API SN	Kinematic Viscosity, cSt @ 100°C	18.20
	Viscosity Index,	148
	Pour Point, °C, Max.	-30
	Flash Point, COC, °C	220
	CCS @ -20 °C, cP, Max.	6700

Available configurations:6 x 1L case, 4 x 4L case

This information only applies to products manufactured in the following location(s) – Singapore