

ES COMPLEAT EG PREMIX

Co-branded with Cummins Filtration, Fleetguard USA, ES Compleat EG Premix is a Heavy duty fully formulated antifreeze/coolant. It is compatible with gaskets, elastomers and other non-metallic in the engine and contains proprietary scale inhibitors.

Extended service life coolant is at 250,000 kilometer and/or 4000 engine hours. Compatible with all other antifreeze/coolants, it is highly recommended for all diesel, gasoline and natural gas engines.

PRODUCT PERFORMANCES

- ASTM 6210, D498
- CID-A-A-52624
- Cummins SB3666132/CES 14603
- Mack 014617004
- John Deere 8650-S
- JIS K2234
- TMC RP329
- Waukesha 4-1974D
- Detroit Diesel 7SE298
- EMD MI 1784E
- Freightliner 4822880
- GM 6038M

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	TYPICAL RESULTS
Colour	Blue
Specific Gravity @ 60°F (15.56 °C)	1.072
Specific Gravity @ 68°F (20 °C)	1.07
Density	8.944 lb/gal (1.072 kg/L)
pH (Undiluted)	10
Reserve Alkalinity (Undiluted)	3
Freeze Point, °C (Undiluted)	-35.8°F (-37.68°C) min
Boiling Point, °C (Undiluted)	226°F (107.78°C)
Water by Weight (approx.)	48.99% max
Total Glycol by Weight	50.19% min
Glassware Corrosion Test	Pass
Water Pump Cavitation Test	Pass
Aluminium Corrosion Test	Pass
Simulated Service Test	Pass
Ash Content by Mass	0.40%
Chloride by Weight	< 25 ppm