Product Information

A PRODUCT OF VALVOLINE INC. USA



VALVOLINE SYNPOWER MOTOR OIL SAE 0W-20

SYNPOWER SAE 0W-20 is a premium fully synthetic motor oil formulated with the highest quality synthetic base oils and enhanced with the most advanced additive technology for ultimate performance in meeting the latest requirements for modern engines. The SYNPOWER SAE 0W-20 is specially designed to provide very high levels of fuel efficiency and deposit protection under severe service conditions and meets the performance requirements of virtually all naturally aspirated, turbocharged and supercharged passenger cars including European and Asian passenger cars. SYNPOWER SAE 0W-20 is specified for use in all Passenger Cars with Gasoline, Diesel, CNG or LPG Engines where in SAE 0W-20 is specified for use. Also recommended for use in all Hybrid models like Toyota , Honda , Mazda etc., where in SAE 0W-20 grade is specified for use .

The Valvoline SYNPOWER Motor Oil Advantages

- Breakdown Resistance: Increased thermal and oxidation stability.
- Deposit Control: Reduces formation of sludge and varnish deposits.
- Wear Protection:
 Improves oil film strength and breakdown resistance.
- Cold Start Properties:
 Flows easily at low temperature.
- Fuel Efficiency : Provides very high level of fuel efficiency and maintains the same for the life of the oil

Approvals / Performance Level

API SN – RC ILSAC GF-5

Typical Characteristics

Kinematic Viscosity, cSt @ 100°C	8.7
Viscosity Index	172
TBN, mg KOH/g (ASTM D-2896)	7.9
Pour Point, °C,	-45
Flash Point, COC, °C	220
CCS @ -35 °C, cP	5600
CCS @ -35 °C, cP	5600

Available configurations:

This information only applies to products manufactured in the following location(s) - Singapore