

Valvoline Hydraulic Oil 68

Anti Wear Hydraulic oil formulated for industrial machinery and earth moving equipment.

Valvoline Hydraulic Oil 68 is a good quality hydraulic oil, formulated with premium mineral base oils and anti-wear additives to offer solid hydraulic performance in a wide range of applications. Valvoline Hydraulic oil is available in viscosity grade ISO VG 68

Performance levels

DIN 51524 (Part 2) HLP

Applications :

For mobile and static hydraulic applications of industrial and other equipment.

Hydraulic cranes and lifts, loaders, reach trucks, forklifts, excavators, dumpers, loading ramps or similar equipment

Hydraulic systems of metalworking machines, or circulation systems of industrial machinery.

Features & Benefits

Solid performance

Formulated with high quality mineral base oils and specific additives to protect against corrosion, foaming and sludge forming.

The product also protects the hydraulic system against rust and corrosion when working in a moist environment.

Consistent viscosity

The product stays in grade during use and shows good viscosity-temperature behavior.

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Kinematic Viscosity, cSt @ 40°C	67.3
Viscosity Index	102
Pour Point, °C, Max.	-24
Flash Point, COC, °C	220
Rust Test D665, A&B, 24 hrs.	Pass
Demulsibility D1401, 40-37-3, minutes, max.	30

Available configurations: 1 x 18 L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
Jan 19

Authors Initials
AS

Product code